

PARLAWOOD



PARLAWOOD

WOOD PANELLING AND WOOD CLADDING

ParlaWood wood panelling and wood cladding are manufactured by gluing four or more uniform slats depending on the width. Because of the structure they are excellent in keeping their shape, and do not crack or have flaws typical for wide solid wood. The appearance is very high-quality.

ParlaWood wood cladding is manufactured by *spruce* and is available in prime painted in addition to unfinished surface. Wood panelling is manufactured by *pine* and there are three primary colours available for the surface treatment of the panelling in addition to unfinished and white lacquered: *traditional grey, ruddy brown and hazel*. Surface treatment for ceiling panelling is white lacquered.

ParlaWood wood panelling and wood cladding bring massive appearance and traditional Finnish atmosphere to your external and internal finishes.



Product details:

WOOD CLADDING, Spruce

Measurements:

Width: 274 mm (260 mm)

Length: 3850 mm , 4150 mm

Thickness: 26 mm, 40 mm

Profile:

STV, microbevelled edges

Gluing:

Water proof 2-component

Package:

Shrink-wrap film 1-2 pcs/package

Fixing:

Concealed screwing or nailing

WOOD PANNELLING, Pine

Wall:**Measurements:**

Width: 220 mm, 274 mm

Length: 3850 mm , 4150 mm

Thickness: 19 mm, 26 mm

Profile:

STV, microbevelled edges

Gluing:

Moisture resistant D4

Package:

Shrink-wrap film 2-3 pcs/package

Fixing:

Concealed screwing or nailing

Ceiling:**Measurements:**

Width: 220 mm (208 mm)

Length: 1800 mm

Thickness: 19 mm

Profile:

STV, STV, microbevelled edges

Gluing:

Moisture resistant D4

Package:

Shrink-wrap film 4 pcs/package

Fixing:

Concealed screwing or nailing



PARLAWOOD

Manufacturer:

PARLATUOTE OY

Teollisuustie 1, FI-58900 Rantasalmi

P O Box 59, FI-58901 Rantasalmi

Tel. +358 20 791 9700

Fax +358 20 791 9839

www.parlatuote.fi